

**THE ART OF
CONTROL**

Neuffener Strasse 29
D-72636 Frickenhausen
Tel: (+49) 7025 - 911 007
Fax: (+49) 7025 - 911 008
Email: info@h-c-s-gmbh.de
www.h-c-s-gmbh.de



COMMISSIONING UNIT FOR DAC-4

CU/DAC-4

**FOR COMMISSIONING, TESTING, TROUBLE SHOOTING
FOR ALL SYSTEMS WHERE DAC-4 BOARDS ARE USED**

- For commissioning, maintenance, tests etc of machines, systems, equipment, valves or for laboratory use
- Universal usable for all versions DAC-4 *1



- Integrated wide range power supply
- Basically all functions of DAC-4 can be tested by means of switches, potentiometers and I/O connections at front and rear
- Versions in 24 V or 12 V available

*1: DAC-4 must be ordered separately!

1 Applications and usage

CU/DAC-4 are generally used for:

For all systems where DAC-4 boards are used

- for commissioning
- for testing
- for maintenance of all systems, machines, installations, equipment applications etc.
- during trouble shooting
- in laboratories
- used in conjunction with one DAC-4

- Basically all digital and analogue I/O signals of DAC-4 are accessible through 4 mm jacks at rear of unit
- Most of the signals can also be generated (or simulated) at the unit itself
- Digital signals are applied by means of toggle switches (for selection of set points, direction, enable signal etc.)
- For analog signals potentiometers and switches are used in order to apply signals to set point and feedback inputs
- Additionally the 24 V supply voltage and the reference voltage of +/- 10 V is available at jacks
- 2 x 3 jacks at rear for connection of solenoid A and B
- Mains cable for European countries included. Other on request
- Optional available for 12 V systems
- The DAC-4 is not included in the delivery. Please order separately.

2 Features

- Compact and light unit; easy to transport, rugged design
- 19" Rack 42TE built into a standard metal housing with carriage handles
- Wide range power supply included for easy world wide usage
- Unit is tested for safety of the insulation and effectiveness of the PE connection

3 Main technical data

Feature	Range, characteristics
Supply voltage	Wide range power supply. Schroff type: MAX 124; 13100-105 Nominal/operational: 100 - 240 V AC / 90 - 254 V; 50 / 60 Hz Mains/line current @ 90 VAC: 1.6 A Efficiency: 75 % Current at switch-on (@ 230 VAC): < 20 A Output parameters: max. output W (50° C): 100 / 80 W Output voltage: 24 V Output current: 4.2 / 3.2 A (< 50° C) / : 3.2 / 2.6 A (70° C) Short-circuit protection Mains/line fuse (high breaking slow): 4 A / 250 VAC, 5 x 20 mm EN60127-2/V Ambient temperature operation/storage: 0 + 70° C / - 20 ... + 85° C Detailed data sheet and CE declaration on request or download from: http://www.pentairprotect.de/de/emea/13100-105-3 . <u>Version with 12 V output voltage on request!</u>
Card slot	For 1 DAC-4 board. 10 TE wide with two rails and connector DIN 41 612, 48 pol. form F
Front elements	1 x switch power on/off; 1 x switch selection direction; 1 x switch enable 8 x switch digital inputs set point, reset ramp and digital inputs general 2 x switch analogue command selection; 2 x switch analogue feedback selection 2 x 10-turn potentiom. analogue command; 1 x 10-turn potentiom. analogue feedback
Rear elements	1 x Main in receptable (IEC 60320-1 / C13) combined with fuse; 1 x mains on/off switch 1 x separate fuse 14 x groups of 4 mm jacks for all kinds of analogue and digital I/O signals (35 jacks total) 1 x 3.5 mm jack for analogue command (tip and sleeve connector)
Housing	Compact housing with two handles Housing configuration: ventilated (IP20) Material: complete metal Dimensions approx.: (w x h x d) 235 (247) x 132 x 256 (300) mm (42 TE / 3 HE) Weight: 3.2 kg (without cables and DAC-4)
Unit tested	In accordance with VDE 0701-1/9 and BGV A3

4 Safety and other remarks



Only authorized and trained personal should perform work at and with this unit

Before connecting the unit to mains supply make sure that nothing is damaged!

Warning: Do not connect the unit if the mains cord or the unit itself is damaged or if the protective earth connection is not effective!



Disconnect mains before opening the unit!

Attention: Danger of electrical shock!

The mains supply cord must be equipped with protective earth (PE green/yellow)!

The mains input is including a fuse and is on the rear side (F1: 2.5 A T for 220/240 V AC)


An additional fuse is placed above the mains connector. This fuse is protecting the secondary circuit (F2: 2,5 A T)



Some output signals are only present when a DAC-4 board is inserted.

5 Front view


Front control elements of CU/DAC-4:



#	Feature, element
1	Wide range power supply. Schroff type: MAX 124; 13100-105 Details see previous page!
2	DAC-4 board; all versions possible. Please order separately.
3	Power on/off for DAC-4
4	Digital input „Direction +“ / „Direction -“
5	Digital input „Enable“
6	Digital inputs „Set point 1 - 4“ („Sp1“, „Sp2“, „Sp3“, „Sp4“)
7	Digital inputs „Reset Ramp“ (Rp0); Digital „I/O 1 - 3“ („Io1“, „Io2“, „Io3“)
8	Selection switches for analogue command input „S1.05“ and „S1.06“
9	10 turn potentiometers for analogue command input „S1.05“ and „S1.06“
10	Selection switches for analogue feedback input „Fb1“ and „Fb2“
11	10 turn potentiometer for analogue feedback input „Fb1“ / „Fb2“

6 Rear view

Rear connection elements of CU/DAC-4:




#	Feature, element
1	Mains on/off switch (illuminated)
2	Secondary fuse F2 (2.5 A T)
3	Mains in receptable
4	Primary fuse (2.5 A M)
5	Label for performed BGV A3 test
6	Digital output „Error“ (24 V)
7	Digital inputs „Enable“ and Reset Ramp“
8	Digital outputs „Comparator“ and „Break“ (24 V)
9	Digital inputs „Set point 1 - 4“ („S1.01“, „S1.02“, „S1.03“, „S1.04“, „S1.08“, „DIO1“)
10	Analogue input set point „S1.06“
11	Digital I/O „DIO2“, „DIO3“
12	Digital inputs „Direction +“, „Direction -“
13	Supply out 24 V DC
14	Analogue input set point „S1.05“; 3 mm jack
15	Reference voltage out „+ 10 V DC“, „-10 V DC“
16	Analogue input feedback 1 and 2 „Fb1“, „Fb2“
17	Analogue output „+/- 10 V“
18	Analogue input set point current „S1.07“
19	Solenoid output A „IA“
20	Solenoid output B „IB“

7 Accessories and Options


Name	Description
DAC-4	Please order separately. Refer to DAC-4 data sheet for details
HCSTool	Software for parameterization, operation, monitoring, storage and documentation of adjustments. In English, French and German on CD (free download available). Please follow this link in order to download the most recent version of HCSTool: http://www.h-c-s-gmbh.de/download/
DAC-4-PC-2xDS9F	Interface cable for communication between PC and DAC-4 for direct usage at RS232 interface; 2 x Sub-D 9-pole connector female
USB-RS232-DS9F	As above but w. USB-adaptor. 1 x connector Sub-D 9-pole, w. 2,5 or 10 m cable
EKB-04	EKB-04 Handheld keypad and display unit for parameter setting and copying

Not to scale!

DAC - all versions *1			
			
HCSTool	Interface Cable	Interface Cable	EKB-4
			

*1: CU/DAC can not be used for DAC-4 with PROFIBUS interface!

8 Ordering code



Ordering code example:

Version with 12 V power supply and standard european mains cable

CU/DAC-4-S12V

9 Our partners and distributors

Europe**NORWAY, ALL NORDIC COUNTRIES****Servi Hydranor AS**

Rasmus Solbergs vei 1
N-1400 Ski
Norway
Tel.: (+47) 64 - 979 797
Fax: (+47) 64 - 979 899
Borre.Kleven@servi.no
www.servi.no

SWEDEN I (South-West)**PMC Hydraulics AB**

Askims Verkstadsväg 15
Box 1013
SE-43621 Askim
Sweden
Tel.: (+46) 31 - 28 98 40
Fax: (+46) 31 - 28 64 01
Per-Anders.Kallden@pmchydraulics.se
www.pmchydraulics.se

SWEDEN II (North-East)**Norrlands Hydraulik**

Stenhuggargatan 4
SE-913 35 Holmsund
Sweden
Tel.: (+46) 70 - 646 57 57
kurt.w@norrhyd.se
www.norrlandshydraulik.se

SWITZERLAND**GRIBI Hydraulics AG**

Lättenstr. 33
CH-8952 Schlieren
Switzerland
Tel.: (+41) 1 733 - 40 50
Fax: (+41) 1 730 - 58 05
info@gribi-hydraulics.ch
www.gribi-hydraulics.ch

GREAT BRITAIN**Voith Turbo Ltd.**

6 Beddington Farm Road
Croydon, Surrey
England CRO 4XB
Tel: (+44)208 667 0333
Fax: (+44) 208 667 0403
nick.moody@voith.com
www.uk.voithturbo.com

FRANCE**SEFYDRO**

Pôle République 1
23, Rue des Entrepreneurs
BP 1086
F-86060 POITIERS
Tel. : (+33) 549 607 016
Fax. : (+33) 549 602 480
bureau.etudes@sefydro.fr
www.sefydro.fr

ITALY**BIMAL TESTING MACHINES S.R.L.**

Automation & Software Department
Zona Industriale - Via A. Monni, 18
I-06135 Ponte Vallecceppi (Perugia)
Italy
Tel.: (+39) 075 - 592 171
Fax: (+39) 075 - 592 1740
automazioni@bimal.com
a.paolucci@bimal.com
www.bimal.com

SPAIN I**HRE HIDRAULIC S.L.**

C / Ibaitarte, 21
E-20870 Elgoibar
Spain
Tel.: (+34) 943 - 742 130
Fax: (+34) 943 - 742 708
hre-hidraulic@hre.es
www.hre.es

SPAIN II**GLUAL HIDRAULICA, S.A.**

Landeta Hiribidea, 11
E-20730 Azpeitia (Gipuzkoa)
Spain
Tel.: (+34) 943 157 015
Fax: (+34) 943 157 404
j.valverde@glual.es
www.glual.com

9 Our partners and distributors

ROW I**USA I****SERVI FLUID POWER INC.**

22240 Merchants Way | Suite 100
Katy, TX 77449, USA
Tel.: (+1) 281 - 347 8080
info@servi-inc.com
www.servi-inc.com

USA II**NC SERVO TECHNOLOGY INC.**

38422 Webb Drive
Westland, MI 48185-1974, USA
Tel.: 1-800 327 - 3786
Tel.: (001) 734 - 326 6666
Fax: (001) 734 - 326 6669
sales@ncservo.com
www.ncservo.com

USA III**Hawe Hydraulik - East**

9009-K Perimeter Woods Drive
Charlotte, NC 28216, USA
Tel: (+1) 704 509 1599
Fax: (+1) 704 509 6302
sales@hawehydraulics.com
www.hawe.com

USA IV**Hawe Hydraulik - Central**

10920 W. Sam Houston Pkwy N.
Suite 700
Houston, TX 77064
Tel: (+1) 713 - 300 3260
Fax: (+1) 281 - 970 6692
sales@hawehydraulics.com
Also:
Cell: (+1) 832 - 797 4608
m.paxton@hawehydraulics.com
www.hawe.com

USA V**Hawe Hydraulik - West**

912990 S.E. HWY 212
Clackamas, OR 97015, USA
Tel: (+1) 503 222 3295
Fax: (+1) 503 225 5976
sales@hawehydraulics.com
www.hawe.com

CANADA and USA VI**HYDRA-FAB
FLUID POWER INC.**

3585 Laird Road Unit 5
Mississauga, Ontario L5L 5Z8
Canada
Tel.: (+1) 905 - 569 1819
Fax: (+1) 905 - 569 7801
rgores@hydrafab.com
www.hydrafab.com

BRASIL, SOUTH AMERICA**Voith Turbo Ltda**

Av. Fernando Stecca, 575
Alto da Boa Vista
BR - 18087 - 450 Sorocaba / SP
Tel.: (+55) 15 228 1114
Fax: (+55) 15 228 1115
friedrich.guthier@voith.com
www.hl-hydraulic.com

9 Our partners and distributors

ROW II**ASIA****KC Kim Consulting GmbH**

Support in German, English,
Chinese and Korean
Industrial Engineering Im- und Export
Lilienthalstr. 3
D-30916 Isernhagen
Tel: +49 (0)511-898809-17
Fax: +49 (0)511-898809-29
c.kim@kc-co.com
info@kc-co.com
www.kc-co.com

AUSTRALIA I (Brisbane)**Hydraulic Specialists
Australia Pty Ltd**

21 Production Street, Wacol
Queensland,
Australia, 4076
Tel: +61 (07) 3879 4400
Fax: +61 (07) 3879 4333
brisbane@hsaus.com.au
lharley@qldhsaus.com.au
www.hsaus.com.au

AUSTRALIA II (Melbourne)**Hydraulic Specialists
Australia Pty Ltd**

9 National Drive , Hallam
Victoria
Australia, 3803
Tel: +61 (03) 9796 5433
Fax: +61 (03) 9796 4955
melbourne@hsaus.com.au
lharley@qldhsaus.com.au
www.hsaus.com.au

INDIA**Greentech Engineers Australia**

Mr. Vish Karegowda
Mount Waverley, Victoria
Australia, 3149
Tel : +61(03) 9803 5941
contact@greentechea.com.au
www.greentechea.com.au
Skype : grnhorizon